



Optimisation of green hydrogen supply chains in Chile

1st LATAM Meeting on Green Ammonia and Power-to-X

Francisca Jalil Vega, Research Fellow in Hydrogen Systems, UCL

Co-investigators: Tito Homem-de-Mello, Nicolás Allendes, UAI

Pedro Vargas, Enzo Sauma, David Pozo, MIGA


f.jalil-vega@ucl.ac.uk



THE BARTLETT
ENERGY INSTITUTE


Agenda

1. Introduction
2. Methodology: Off-grid model
3. Results
4. Costs discussion
5. Methodology: On-grid model
6. Results comparison
7. Conclusion




Introduction

- Chile's NDC:
 - Commitment to reach net-zero carbon emissions by 2050, with intermediate carbon budgets
 - Reduction of black carbon emissions by 25% with respect to 2016 levels over the next decade
- Hydrogen, when produced from low-carbon supply chains, has been recognised as a potential alternative for decarbonising “hard-to-abate” sectors (heavy duty transport, shipping, aviation, industry, heating)
- Chile has the potential to produce low-cost green hydrogen production
- How would such hydrogen supply chains (HSC) look like, and what are their environmental and economic implications?



Questions

- Where to build generation and transport infrastructure to make optimal use of existing resources?
 - Where to install solar/wind plants and what is their optimal capacity
 - Where to install electrolysis technologies, which technologies and what capacity
 - What do we transport? From/to where? (water, electricity, hydrogen)
- How to configure and operate the supply chains considering variable energy supply?
- How to produce hydrogen with limited water resources?
 - Location and capacity of water desalination and transport




Methodology – Off-grid model

- We propose a **geographically explicit** linear optimisation model for green hydrogen supply chain (HSC).
- The model **minimises** the **levelised cost of hydrogen** (LCOH) for a planning horizon between **2025-2050**, using typical days and **hourly** resolution.
- Investment decisions every 5 years
- **6 demand scenarios**: E1 (demand for exports), and E2 (domestic demand)
- Model decides:
 - Locations and capacities of wind and solar generation technologies
 - Locations, capacities, and types of electrolysers
 - Locations and capacities of desalination plants
 - Capacities and layouts of electricity lines, water pipelines, and hydrogen transport (trucks and pipelines)
 - Hourly operation of technologies



Annual hydrogen demand (Mt).
E1: Demand for exports
E2: Domestic demand

Year	E1.3	E1.5	E1.10	E1.15	E1.20	E2
2025	0	0	0	0	0	0.011
2030	0.11	0.19	0.38	0.57	0.77	0.023
3035	0.27	0.45	0.91	1.37	1.82	0.035
2040	0.43	0.72	1.44	2.16	2.88	0.046
2045	0.59	0.98	1.97	2.95	3.94	0.046
2050	0.75	1.25	2.5	3.75	5	0.046



Methodology


- Modelled area: SEN
- 2 scenarios
 - Domestic demand
 - Demand for exports
- Candidate zones for installing desalination plants
- Renewable potential clusters – candidates for installing wind/PV generation plants (50 GW/650 GW)



Methodology


- Modelled area: SEN
- 2 scenarios
 - Domestic demand
 - Demand for exports
- Candidate zones for installing desalination plants
- Renewable potential clusters – candidates for installing wind/PV generation plants (50 GW/ 650 GW)

Example: Zone 1, wind profiles





Renewable potentials

- Wind potential
- Solar PV potential



Methodology

- Modelled area: SEN
- 2 scenarios
 - Domestic demand
 - Demand for exports
- Candidate zones for installing desalination plants
- Renewable potential clusters – candidates for installing wind/PV generation plants (50 GW/ 650 GW)



Methodology

- **Model**

- Flows




- Electricity
 - Hydrogen
 - Water

- Transport modes

- Electricity: Transmission lines
 - Hydrogen: Pipelines, liquid hydrogen trucks
 - Water: Pipelines

- Conversion technologies



- Electricity generation: PV, wind turbines
 - Electrolysis: PEM
 - Desalination: Reverse osmosis



Methodology – Model formulation

Constraints and objective function

$$LCOH = \frac{\sum_{t=2025}^{2050} \frac{I_t + O\&M_t - RV_{2050}}{(1+r)^{t-2020}}}{\sum_{t=2025}^{2050} \frac{H_2 Demand_t}{(1+r)^{t-2020}}}$$




Results

Total hydrogen demand for planning horizon (Mt)

E1.3	E1.5	E1.10	E1.15	E1.20	E2
7.81	13.03	26.06	39.06	52.08	0.86

LCOH decomposition and emission factors for export scenarios



- Main results for domestic and exports scenarios:


- Export scenarios:

- LCOH: 4.31 – 4.46 USD/kg
- Emission factors: 0 – 5.12 kgCO₂/tonH₂
- Water consumption: 70 – 469 Mt

- Domestic demand scenarios:


- LCOH: 6.26 USD/kg
- Emission factor: 1.09 kgCO₂/tonH₂
- Water consumption: 7.76 Mt

- Different demands lead to different HSC configurations




Results

- Exports scenario E1.5 – 2050
 - Infrastructure concentrated in northern regions
 - Hydrogen production in interior zones
 - Both renewable sources used for electricity generation (PV, wind)
 - Water distributed to interior zones
 - No use of H₂ trucks





- Demand zones
- 52-241 kg H₂O/s RO desal.
- 0.4-3.1 GW PEM
- 0.9-3.6 GW wind turbines
- 5.04-9.87 GW PV
- 0.4-1.9 GW H₂ pipelines
- 73-194 kg H₂O/s H₂O pipelines
- 0.001-1.22 GW elec. trans.





Results

- Exports scenario E1.20 – 2050
 - Higher installed capacities of technologies and transport infrastructure
 - Increase of LCOH
 - Hydrogen production in interior zones: PV and wind, mostly PV
 - Incorporates the use of H₂ trucks for H₂ transport
 - New zones of H₂ production



Results

- Domestic demand scenario E2 – 2050
 - Smaller capacities
 - Infrastructure concentrated in southern regions
 - Mainly wind turbines for electricity generation
 - Hydrogen produced in coastal and demand zones



Costs discussion


- Hydrogen for exports cost comparison

Destination	Distance (km)	Final calculated LCOH ¹ (USD/kg)	Local green H ₂ LCOH ² (USD/kg)	Local blue/grey H ₂ LCOH ² (USD/kg)	Competitiveness against local green H ₂ production	Competitiveness against local blue/grey H ₂ production
Osaka, Japan	17500	6.86-7.01	6.89-7.31	3	X	X
LA, USA	8500	6.33-6.48	8.01-9.13	2-2.78	✓	X
Busan, South Korea	17500	6.86-7.01	8.11-12.6	6.17	✓	X
Hamburg, Germany	14500	6.69-6.84	6.96-19.14	2.73	✓	X
Shanghai, China	18500	6.91-7.06	8.3-15.8	1.2-3.46	✓	X

¹Assumptions:

- Levelised cost of liquefaction 1.5 USD/kg
- Levelised cost of shipping: Distance dependent

²Costs from literature survey




On-grid model

Methodology – On-grid model


- Energy systems model OSeMOSYS [1].
- Minimum cost optimisation considering whole system's growth and operation
- 19 nodes and 23 transmission lines
- Investment periods every 5 years (2025 to 2060).
- 4 typical days, hourly resolution
- Hydrogen demand from *Accelerated Transition* scenario PELP.
- Generation potentials, installed capacities, projects under construction, fuel costs, hourly availability of variable renewables, CAPEX, OPEX
- **Additional constraints:** Emissions limit for the whole period of H₂ production of 28.2 gCO₂/MJ (EU)
- **H2-Ref and H2-Limit scenarios:** On-grid production **without** and **with** emissions limit




[1] Howells et al. 2011 . <http://dx.doi.org/10.1016/j.enpol.2011.06.033>




Methodology – Energy system




Results



Energy balance 2040
H2-Ref scenario (TWh)





Energy balance 2040
H2-Lim scenario (TWh)



Results


- LCOH:
 - H2-Ref: 3 USD/kg
 - H2-Limit: 3.14 USD/kg
 - (Previous: 4.31 – 4.46 USD/kg)
 - H2_Limit: Emission factor does not exceed 28.2 gCO₂/MJ

Emission factor CO₂ for hydrogen supply chain
(Scenarios H2-Ref and H2-limit)



Conclusion

- Different assumptions (spatial resolution, location and magnitude of demands)
- LCOH:
 - Off-grid exports: 4.31 – 4.46 USD/kg
 - Off-grid domestic demand: 6.26 USD/kg
 - On-grid green: 3.14 USD/kg
- Optimal HSC configuration:
 - Off-grid exports:
 - Concentrated in the north: **PV**, wind
 - Hydrogen production in interior areas
 - Off-grid domestic demand:
 - Concentrated in the south: **wind**
 - Production near demand and coast
 - On-grid green:
 - Concentrated in the north: **PV**
- Competitiveness for exports
 - Sensitive to technoeconomic assumptions
 - Potentially competitive compared to local green hydrogen production
 - Not competitive against blue/grey hydrogen
- Current/future work
 - Hourly operation for whole year, include hydrogen and electricity storage, and operational constraints for alkaline electrolyzers
 - Environmental impacts of brine production, and H₂ leakage GWP
 - Off grid versus on-grid production scenarios



Thank you for listening

Francisca Jalil-Vega, Research Fellow in Hydrogen Systems,
f.jalil-vega@ucl.ac.uk
ucl.ac.uk/bartlett/energy @UCL_Energy